

Safeclean HD November 2007

Degreasing agent.

DESCRIPTION

Safeclean HD is a degreasing agent that will clean a substrate from normal grease, oil, diesel, dirt from smoke etc.

ADVANTAGES

Safeclean HD is an environmental friendly product that will be broken down in the nature. It is easy to use.

SPECIFICATIONS

Gravity weight	1,06
Boiling point	100°C
PH	11,5
Solubility in water	100%
Viscosity	26 cP

DILUTIONS

Normal dilution is:
1 part Safeclean HD : 20 parts of clean water.

NB!! On coatings, paint, glass etc. a concentration stronger than 1:20 can cause discoloration.

TEMPERATURE LIMITATIONS

All work has to be done above 0°C. At low temperatures the effect to clean is poorer. Best results are achieved at 20°C and above.

CLEANING INSTRUCTIONS

1. Either pour the diluted Safeclean HD in a low-pressure spray equipment or pour it straight on the surface to be cleaned.
2. Let the solution work for 5 minutes. If it dries in spots pour on more.
3. Give it a light scrub with a soft brush
4. Use a high-pressure washer to rinse off the solution.
5. If there is spots that are not clean after this operation, you should increase the concentration of Safeclean HD and repeat the procedure.

PACKING

The Safeclean HD is supplied in plastic containers of 25 l and 5 l.

STORAGE

The Safeclean HD shall be stored frost free. The shelf life is minimum 1 year if kept in the container with the lid tightly closed.

HEALTH AND SAFETY

Please see our health and safety datasheet.

TECHNICAL SERVICE

Please contact Fjerby for further information.

All the data and suggestions in this datasheet are based on tests and experiences. As the users working conditions is out of our control, we cannot take the responsibility for the results that the user obtains by using the product.